



MAGN1565



汽車規範 Specifications

| | |
|------------------|--|
| General Motors | GM7114M · GMW3359 |
| Ford | S439(WSS-M21P37-A1) |
| Chrysler | PS-10633 · PS-10378 |
| ArvinMeritor | P91 |
| ASTM | F1137 Type III |
| Bobcat | PS-106A |
| BMW | GS90010 |
| Case New Holland | MAT0320 Type I Class A |
| Daimler-Benz | DBL 8440 |
| Delphi | DX551801 · DX45501804 DX551810 · DX44501804 |
| Fiat | 9.57513/Tipo IV |
| Int'l Truck | TMS-4518 Type I MPAPS G-4518 Type I |
| ISO | 10683 |
| JLG | 4150701 |
| John Deere | JDM F13 |
| Land Rover | LRES.21.ZS.05 |
| Nissan | NES M4601 |
| Porsche | PTL 7529 |
| PSA | B15 3320 |
| Renault Trucks | 01.71.4002/H |
| Tacom/US Army | 12469117 |
| Trane | S 3201063A1 |
| Tesla | TM-0010F-M |
| TRW | TS2-25-060 Class A |
| Volkswagen | TL233 |
| Volvo | VCS5737.29,.19 |

效能 Performance Data

| | |
|---------------------------|-----------------------------|
| 鹽霧 Salt Spray | 480~100hrs (依各汽車規範或客戶要求) |
| ASTMB117 | |
| 平均膜厚 Coating Thickness | 12µm . (依各汽車規範或客戶要求) |
| 顏色 Color | 銀灰 Silver/Gray |